

# AIR CONDITIONING ACCESSORIES LTD



## PRODUCT ADVANTAGES

- > ECO DCI Window.
- > New and refrigerant R32 environmental friendly.
- > Unique design that can reach the ECO design requirements and 1W in standby.
- > Design and working with R-32 that is one of the lowest Global Warming Potential (GWP).
- > High efficiency that can reach SEER over 5.0.
- > Bi operation methods, on unit or by remote control.



WFD RC

## [ TECHNICAL DATA ]

Indoor units		AWWR-WFD009-C11	AWWR-WFD012-C11
<b>COOLING</b>			
Rated capacity	kW	2.75	3.7
Pdesignc	kW	2.75	3.7
Rated power input	kW	0.81	1.09
SEER/Energy label		5.10/A	5.10/A
Operating limits	°C	18°/ 43° Dry bulb	
<b>INDOOR UNIT</b>			
Sound pressure level to 1 m (LS/MS/HS)	dB(A)	45/47/49	45/47/49
Airflow (LS/MS/HS)	m³/h	310/350/380	400/450/490
Dehumidification	l/h	1.0	1.2
Compressor type		Rotary	Rotary
Outline dimensions (WxHxD)	mm	560x375x710	660x428x700
Package dimensions (WxHxD)	mm	623x425x806	739x515x793
Net weight/Gross weight	kg	34/36.7	46/50
Part number		7WT010008	7WT010009
<b>POWER SUPPLY 1~230V - 50 HZ</b>			
Power supply side		Indoor	Indoor
Power cable section	mm²	3x1.0	3x1.5
Fuse rating am	A	10	10